


# Blanking Plug with captive seal Metric cyl



## Drawing



Part n°	R1	ØD	L	L1	HEX 1	Working Pressure (bar)
<b>STOPFEN M 10X1</b>	M10X1	13	12	8	5	400
<b>STOPFEN M 12X1.5</b>	M12X1.5	16.9	17	12	6	400
<b>STOPFEN M 14X1.5</b>	M14X1.5	18.9	17	12	6	400
<b>STOPFEN M 16X1.5</b>	M16X1.5	21.9	17	12	8	400
<b>STOPFEN M 18X1.5</b>	M18X1.5	23.9	17	12	8	400
<b>STOPFEN M 20X1.5</b>	M20X1.5	25.9	19	14	10	400
<b>STOPFEN M 22X1.5</b>	M22X1.5	26.9	19	14	10	400
<b>STOPFEN M 26X1.5</b>	M26X1.5	31.9	21	16	12	400
<b>STOPFEN M 27X2</b>	M27X2	31.9	21	16	12	400
<b>STOPFEN M 33X2</b>	M33X2	40	22,5	16	17	400
<b>STOPFEN M 42X2</b>	M42X2	26.9	19	14	22	315
<b>STOPFEN M 48X2</b>	M48X2	26.9	22,5	16	24	315

**TAON**

Hydraulik Komponenter

TAON Hydraulic Components ApS are specialists in hydraulic solutions, components and tools.

• +45 24 48 84 80 • info@taon.dk • www.taon-hydraulic.com

© TAON Hydraulic will always help you find the best solution.



PERFORMANCE DATA



TAON Hydraulic Components ApS are specialists in hydraulic solutions, components and tools.

• +45 24 48 84 80 • [info@taon.dk](mailto:info@taon.dk) • [www.taon-hydraulic.com](http://www.taon-hydraulic.com)

© TAON Hydraulic will always help you find the best solution.



**PERMISSIBLE SHAFT SEAL PRESSURE**

**AXIAL AND RADIAL FORCES**

**OIL FLOW IN DRAIN LINE**



TAON Hydraulic Components ApS are specialists in hydraulic solutions, components and tools.

• +45 24 48 84 80 • [info@taon.dk](mailto:info@taon.dk) • [www.taon-hydraulic.com](http://www.taon-hydraulic.com)

© TAON Hydraulic will always help you find the best solution.