

# Ultraflex - hydraulikslange



## CHARACTERISTICS FEATURES

**Specifications: DIN 20022 2SC, EN 857/2SC Construction**

**Tube: seamless oil resistant synthetic rubber reinforcement: 2 high tensile steel wire braids**

**Cover: weather, abrasion and ozone resistant synthetic rubber Temperature range, continuous service: -40°C + 100°C**

**Max operating temperature: + 125° C Fluid resistance: hydraulic oils, both mineral and "biological" polyglycol base oils oil/water emulsions wate**

Inside diameter				Over Wire Daim	Over Cover Diam	Min Burst Pressure	Max Work Pressure	Min Bend Radius	Average Weight
Inches	Dash size	DN	MM	MM	MM	BAR	BAR	MM	G/M
1/4	4	6	6,4	11,3	13,6	1600	400	45	280
3/8	6	10	9,5	15,1	17,6	1320	330	65	410
1/2	8	12	12,7	18,4	20,7	1100	275	80	500
3/4	12	20	19	25,5	27,7	860	215	120	780
1	16	25	25,4	33,5	35,7	660	165	160	1100



TAON Hydraulic Components ApS are specialists in hydraulic solutions, components and tools.

• +45 24 48 84 80 • info@taon.dk • www.taon-hydraulic.com

© TAON Hydraulic will always help you find the best solution.